

ACRYLIC PRIMER

Acrylic Primer is a ready to use primer for use on porous and difficult substrates prior to tiling or screeding or to seal gypsum plasters or screeds prior to the addition of cement based adhesives. It can be used neat when sealing substrates or diluted with an equal quantity of water for general priming.

- Water based polymer emulsion.
- Ready to use primer.
- Improved adhesion.
- Coloured to indicate application.

Technical Information

FORM:	Liquid
COLOUR:	Pink
SPECIFIC GRAVITY:	1 – 1.1 g/ml
pH:	7 – 8
SOLUBILITY:	Miscible with water
BOILING POINT:	100°C (Water based)
FLASH POINT:	No Risk
COVERAGE:	
	When used neat – 1 Litre will cover approx. 7 - 10 m ² When diluted 1:1 with clean water – 1 Litre will cover approx. 14 - 20 m ²

DIRECTIONS FOR USE:

As a Primer: Acrylic Primer should be used to prime all dense and porous surfaces prior to application of any of the range of Larsen Professional Ceramic Tile Adhesives or the range of Larsen Flooring products. On porous surfaces where the requirement is not to seal the surface, dilute Acrylic Primer 1:1 with clean water and apply adhesive/screed etc. while primer is still tacky. (Do not allow to dry.) Particularly porous substrates may require a second coat applied after the first has been allowed to dry. When using Acrylic Primer to seal surfaces e.g. Gypsum plaster, apply neat to the surface (do not allow neat primer to pond), 2 or more coats may be required. Apply adhesive/screed etc. while primer is still tacky. (Do not allow to dry.)

Important: When Acrylic Primer is applied neat care must be taken to ensure skinning of the product and eventual delamination does not occur.

Cleaning Clean tools, equipment etc. using cold water.

Storage Acrylic Primer should be stored in closed containers protected from extremes of temperature.

Shelf Life 12 months in unopened manufacturer's containers.

Packaging 1L and 5L packs

HANDLING PRECAUTION Larsen products are generally harmless provided they are used as instructed and that certain precautions normally taken when handling chemicals are observed eg, do not allow any material to come into contact with foodstuffs. Avoid prolonged contact with skin. Do not swallow. For specific product safety details consult the Material Safety Data Sheet.

IMPORTANT NOTE The information given in this data sheet is based on both current development work and many years' field experience. Whilst every effort is made to ensure that the information is reliable we cannot accept responsibility for any work carried out with our materials as we have no control over methods of application, site conditions etc.

For further information consult our Technical Department
TEL: BELFAST 02890774000 DUBLIN 018348255